



# 9 mm LUGER SUBSONIC / 9 × 19 FMJ

V311662  
150 GRS

Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.

PROPERTIES

|                        |                    |          |       |
|------------------------|--------------------|----------|-------|
| BULLET                 | TYPE               | FMJ      |       |
|                        | WEIGHT             | grs      | 150   |
|                        |                    | g        | 9.70  |
|                        | SECTIONAL DENSITY  | lb/in²   | 0.170 |
|                        | MATERIAL OF JACKET | CuZn 30  |       |
| NUMBER                 |                    | N/A      |       |
| BALLISTIC COEFFICIENT  |                    | G1       | 0.318 |
| CARTRIDGE              | WEIGHT             | g        | 14.1  |
|                        | LENGTH             | mm       | 29.69 |
| CASINGS                |                    | N/A      |       |
| POWER FACTOR ESTIMATED |                    | kg·r·fps | 150.2 |
| +P AMMUNITION          |                    | No       |       |
| TEST BARREL LENGTH     |                    | mm       | 150   |
| SUGGESTED USE          |                    | N/A      |       |
| FEATURES               |                    | N/A      |       |
| PACKAGING              |                    |          |       |
| BOXES PER CASE         |                    | 20       |       |
| WEIGHT PER CASE        |                    | kg       | 14.8  |
|                        |                    | lb       | 33    |

BALLISTICS

|                  |     |        |     |      |       |
|------------------|-----|--------|-----|------|-------|
| DISTANCE         | m   | MUZZLE | 25  | 50   | 100   |
| VELOCITY         | m/s | 305    | 300 | 295  | 286   |
| ENERGY           | J   | 451    | 435 | 421  | 395   |
| DISTANCE         | m   | 12.5   | 25  | 50   | 100   |
| POINTS OF IMPACT | cm  | 0.1    | 0.0 | -5.3 | -37.4 |

